
SPTECH Silicon NPN Power Transistor

DESCRIPTION

- Collector-Emitter Breakdown Voltage-
  : $V_{(BR)CEO}$= 100V(Min)
- Collector-Emitter Saturation Voltage-
  : $V_{CE(sat)}$= 1.5V(Max) @I_C= 3A



APPLICATIONS


- Designed for B/W TV vertical output applications.

ABSOLUTE MAXIMUM RATINGS(T_a=25℃)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	250	V
V_{CEO}	Collector-Emitter Voltage	100	V
V_{EBO}	Emitter-Base Voltage	6	V
I_C	Collector Current-Continuous	3	A
P_C	Collector Power Dissipation @ T_C=75℃	30	W
T_J	Junction Temperature	150	℃
T_{stg}	Storage Temperature Range	-55~150	℃

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j\text{-}c}$	Thermal Resistance,Junction to Case	2.5	℃/W



DIM	mm MIN	MAX
A	39.00	
B	25.30	26.67
C	7.80	8.30
D	0.90	1.10
E	1.40	1.60
G	10.92	
H	5.46	
K	11.40	13.50
L	16.75	17.05
N	19.40	19.62
Q	4.00	4.20
U	30.00	30.20
V	4.30	4.50

SPTECH Silicon NPN Power Transistor

ELECTRICAL CHARACTERISTICS

T_C=25℃ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage	I_C= 5mA; I_B= 0	100			V
$V_{(BR)EBO}$	Emitter-Base Breakdown Voltage	I_E= 1mA; I_C= 0	6			V
$V_{(BR)CBO}$	Collector-Base Breakdown Voltage	I_C= 5mA; I_E= 0	250			V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	I_C= 3A; I_B= 0.3A			1.5	V
$V_{BE(sat)}$	Base-Emitter Saturation Voltage	I_C= 3A; I_B= 0.3A			1.5	V
I_{CBO}	Collector Cutoff Current	V_{CB}= 50V; I_E= 0			0.5	mA
h_{FE}	DC Current Gain	I_C= 2A; V_{CE}= 5V	30		120	

◆ **h_{FE} Classifications**

Yellow	Green
30-80	60-120