
SPTECH Silicon PNP Darlington Power Transistor




DESCRIPTION

- Collector-Emitter Sustaining Voltage-
  : $V_{CEO(SUS)}$= -100V(Min)
- High DC Current Gain
  : h_{FE}= 750(Min) @I_C= -3A
- Low Collector Saturation Voltage
  : $V_{CE(sat)}$= -2.5V(Max.)@ I_C= -3A
- Complement to Type BDX33C

APPLICATIONS

- Designed for general purpose amplifier and low speed switching applications.



DIM	mm MIN	MAX
A	15.50	15.90
B	9.90	10.20
C	4.20	4.50
D	0.70	0.90
F	3.40	3.70
G	4.98	5.18
H	2.68	2.90
J	0.44	0.60
K	13.00	13.40
L	1.20	1.45
Q	2.70	2.90
R	2.30	2.70
S	1.29	1.35
U	6.45	6.65
V	8.66	8.86

ABSOLUTE MAXIMUM RATINGS(T_a=25℃)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	-100	V
V_{CEO}	Collector-Emitter Voltage	-100	V
V_{EBO}	Emitter-Base Voltage	-5	V
I_C	Collector Current-Continuous	-10	A
I_{CM}	Collector Current-Peak	-15	A
I_B	Base Current-Continuous	-0.25	A
P_C	Collector Power Dissipation @ T_C=25℃	70	W
T_J	Junction Temperature	150	℃
T_{stg}	Storage Temperature Range	-65~150	℃

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j\text{-}c}$	Thermal Resistance,Junction to Case	1.78	℃/W

SPTECH Silicon PNP Darlington Power Transistor

ELECTRICAL CHARACTERISTICS

T_C=25℃ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{CEO(SUS)}$	Collector-Emitter Sustaining Voltage	I_C= -50mA; I_B= 0	-100			V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	I_C= -3A; I_B= -6mA			-2.5	V
$V_{BE(on)}$	Base-Emitter On Voltage	I_C= -3A; V_{CE}= -3V			-2.5	V
I_{CBO}	Collector Cutoff Current	V_{CB}= -100V; I_E= 0			-0.2	mA
I_{CEO}	Collector Cutoff Current	V_{CE}= -50V; I_B= 0			-0.5	mA
I_{EBO}	Emitter Cutoff Current	V_{EB}= -5V; I_C= 0			-10	mA
h_{FE}	DC Current Gain	I_C= -3A; V_{CE}= -3V	750			