
SPTECH Silicon NPN Power Transistor



DESCRIPTION

- DC Current Gain -
  : h_{FE} =30@ I_C= 2A
- Collector-Emitter Sustaining Voltage-
  : $V_{CEO(SUS)}$= 80V(Min)
- Complement to Type BD810

APPLICATIONS


- Designed for use in high power audio amplifiers utilizing complementary or quasi complementary circuits.

ABSOLUTE MAXIMUM RATINGS(T_a=25℃)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	80	V
V_{CEO}	Collector-Emitter Voltage	80	V
V_{EBO}	Emitter-Base Voltage	5	V
I_C	Collector Current-Continuous	10	A
I_B	Base Current	6	A
P_C	Collector Power Dissipation @ T_C=25℃	90	W
T_J	Junction Temperature	150	℃
T_{stg}	Storage Temperature Range	-55~150	℃

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j\text{-}c}$	Thermal Resistance, Junction to Case	1.39	℃/W



DIM	mm MIN	MAX
A	15.50	15.90
B	9.90	10.20
C	4.20	4.50
D	0.70	0.90
F	3.40	3.70
G	4.98	5.18
H	2.68	2.90
J	0.44	0.60
K	13.00	13.40
L	1.20	1.45
Q	2.70	2.90
R	2.30	2.70
S	1.29	1.35
U	6.45	6.65
V	8.66	8.86

SPTECH Silicon NPN Power Transistor

ELECTRICAL CHARACTERISTICS

T_C=25℃ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	MAX	UNIT
$V_{CEO(SUS)}$	Collector-Emitter Sustaining Voltage	I_C= 30mA ;I_B= 0	80		V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	I_C= 3A; I_B= 0.3A		1.1	V
$V_{BE(on)}$	Base-Emitter On Voltage	I_C= 4A ; V_{CE}= 2V		1.6	V
I_{CBO}	Collector Cutoff Current	V_{CB}= 80V;I_E= 0		1.0	mA
I_{EBO}	Emitter Cutoff Current	V_{EB}= 5V; I_C= 0		2.0	mA
h_{FE-1}	DC Current Gain	I_C= 2A ; V_{CE}= 2V	30		
h_{FE-2}	DC Current Gain	I_C= 4A ; V_{CE}= 2V	15		
f_T	Current-Gain—Bandwidth Product	I_C= 1.0A ; V_{CE}= 10V; f_{test}= 1.0MHz	1.5		MHz