

Features

- Single and dual section control
- Metal shaft styles
- Carbon element
- Center and multiple detent options
- Wide range of resistance tapers
- Plain or knurled shaft options

BOURNS® PRO AUDIO

PDB18 Series - 17 mm Rotary Potentiometer

Electrical Characteristics

Taper ..... Linear, audio
Standard Resistance Range
..... 1 K ohms to 1 M ohms
Standard Resistance Tolerance ..... ±20 %
Residual Resistance ..... 1 % max.


Environmental Characteristics

Operating Temperature ... -10 °C to +50 °C
Power Rating
Linear ..... 0.2 watt
Dual Section ..... 0.125 watt
Audio ..... 0.1 watt
Dual Section ..... 0.06 watt
Maximum Operating Voltage
Linear ..... 200 V
Audio ..... 150 V
Sliding Noise ..... 47 mV max.

Mechanical Characteristics


Mechanical Angle ..... 300 ° ±5 °
Rotational Torque ..... 10 to 150 gf-cm
Detent Torque ..... 150 to 500 g-cm
Stop Strength ..... 5 kg-cm min.
Rotational Life ..... 15,000 cycles
Soldering Condition
..... 260 °C max. within 3 seconds
Hardware ..... One flat washer and mounting nut supplied per potentiometer with bushing

Derating Curve



Product Dimensions

PDB181-K




SHAFT SHOWN IN CCW POSITION

DIMENSIONS: MM / (INCHES)

SCHEMATIC

PDB181-A



SHAFT SHOWN IN CCW POSITION

*RoHS Directive 2002/95/EC Jan. 27, 2003 including annex and RoHS Recast 2011/65/EU June 8, 2011.

Specifications are subject to change without notice.
The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
Users should verify actual device performance in their specific applications.

Additional Features

- Linear, audio and reverse audio taper options
- RoHS compliant*

Applications


- Audio/TV sets
- Car radio
- Amplifiers/mixers/drum machines/ synthesizers
- PCs/monitors
- Appliances

PDB18 Series - 17 mm Rotary Potentiometer

BOURNS®


Product Dimensions

PDB181-B



SHAFT SHOWN IN CCW POSITION


PDB181-E



SHAFT SHOWN IN CCW POSITION

DIMENSIONS: MM / (INCHES)

PDB181-D





SHAFT SHOWN IN CCW POSITION

Specifications are subject to change without notice.
The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
Users should verify actual device performance in their specific applications.

Product Dimensions


PDB181-P






SHAFT SHOWN IN CCW POSITION


PDB182-B
Dual Gang







SHAFT SHOWN IN CCW POSITION

PDB182-K
Dual Gang





SHAFT SHOWN IN CCW POSITION




SCHEMATIC


DIMENSIONS: MM (INCHES)

Specifications are subject to change without notice.
The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
Users should verify actual device performance in their specific applications.

Product Dimensions


PDB182-E
Dual Gang






SHAFT SHOWN IN CCW POSITION

PDB182-D
Dual Gang






SHAFT SHOWN IN CCW POSITION

DIMENSIONS: MM / (INCHES)

Shaft Styles


K Type

L	15 (.591)	18 (.709)	20 (.787)	25 (.984)	30 (1.181)
A	6.5 (.256)	6.5 (.256)	11.5 (.453)	14 (.551)	19 (.748)




P Type

L	20 (.787)	25 (.984)	30 (1.181)



F Type

L	15 (.591)	20 (.787)	25 (.984)	30 (1.181)	35 (1.378)
F	7 (.276)	12 (.472)	12 (.472)	12 (.472)	12 (.472)





Specifications are subject to change without notice.
The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
Users should verify actual device performance in their specific applications.


PDB18 Series - 17 mm Rotary Potentiometer

BOURNS®

Tapers







How To Order

PDB18 1 - K 4 25 K - 103 A1

Model

Number of Sections
- 1 = Single Section
- 2 = Dual Section

Terminal Configuration (Pin Layout) (see individual drawings)
- K = PC Pins vertical/ Down Facing (12.5 mm)
- A = PC Pins vertical/ Down Facing (18.0 mm)
- B = PC Pins vertical Down Facing (23.0 mm)
- E = Solder Lugs Rear Facing
- P = PC Pins Rear Facing
- D = PC Pins Front Facing

Detent Option
- 2 = Center Detent
- 4 = No Detents
- 5 = 10 Detent / 11 Position
- 6 = 20 Detent / 21 Position
- 7 = 30 Detent / 31 Position
- 8 = 40 Detent / 41 Position

Standard Shaft Length
- 15 = 15 mm
- 18 = 18 mm
- 20 = 20 mm
- 25 = 25 mm
- 30 = 30 mm

Shaft Style
- F = Metal Flatted Shaft
- K = Metal Knurled Type Shaft 18 Toothed Serration Type
- P = Metal Plain Shaft

Resistance Code (See Table)

Resistance Taper (See Taper Charts)
Taper Series followed by Curve Number

Other styles available.

Standard Resistance Table

Resistance (Ohms)	Resistance Code
1,000	102
2,000	202
5,000	502
10,000	103
20,000	203
50,000	503
100,000	104
200,000	204
500,000	504
1,000,000	105

REV. 03/13

Specifications are subject to change without notice.
The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
Users should verify actual device performance in their specific applications.