
DESCRIPTION


The LM317 is an adjustable 3-terminal positive voltage regulator,designed to supply 1A of output current with voltage adjustable from 1.3V ~ 37V.

FEATURES


*Output voltage adjustable from 1.3V ~ 37V
*Output current in excess of 1A
*Internal short circuit protection.
*Internal over temperature protection.
*Output transistor safe area compensation




TO-220




TO-263



SOT-223



TO-220F




TO-252



TO-3

BLOCK DIAGRAM



ABSOLUTE MAXIMUM RATINGS (Ta=25°C, unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Input - Output Voltage Difference	V_{IN}-V_{OUT}	40	V
Power Dissipation	P_D	Internal limited	
Junction Temperature	T_J	+125	°C
Operating Temperature	T_{OPR}	-40 ~ +85	°C
Storage Temperature	T_{STG}	-40 ~ +150	°C

Note:1. Absolute maximum ratings are stress ratings only and functional device operation is not implied. The device could be damaged beyond Absolute maximum ratings.

THERMAL DAT

PARAMETER		SYMBOL	RATINGS	UNIT
Junction-to-Ambient	TO-252	θ_{JA}	112	℃/W
	TO-220/TO-220F		54	
	TO-263		64	
	SOT-223		165	
	TO-3		35	
Junction-to-Case	TO-252	θ_{JC}	12	℃/W
	TO-220/TO-220F		5	
	TO-263		5	
	SOT-223		23	
	TO-3		3	

ELECTRICAL CHARACTERISTICS

(V_{IN}-V_{OUT}=5V, I_{OUT}=10mA, Ta=25°C, unless otherwise specified.)

PARAMETER	SYMBOL	TEST CONDITIONS		MIN	TYP	MAX	UNIT
Line Regulation	$\Delta V_{OUT}/V_{OUT}$	3V≦V_{IN}-V_{OUT}≦40V			0.01	0.04	%/V
Load Regulation	ΔV_{OUT}	10mA≦I_{OUT}≦1A	V_{OUT}≦5V		5	25	mV
			V_{OUT}≧5V		0.1	0.5	%
Adjustable Pin Current	I_{ADJ}				50	100	μA
Adjustable Pin Current Change	ΔI_{ADJ}	3V≦V_{IN}-V_{OUT}≦40V, 10mA≦I_{OUT}≦1A, P_D≦20W			0.2	5	μA
Reference Voltage	V_{REF}	3V≦V_{IN}-V_{OUT}≦40V, 10mA≦I_{OUT}≦1A, P_D≦20W		1.20	1.25	1.30	V
Temperature Stability		T_{MIN}≦T_J≦T_{MAX}			0.7		%/V_{OUT}
Minimum Load Current for Regulation	$I_{L(MIN)}$	V_{IN}-V_{OUT}=40V			3.5	10	mA
Maximum Output Current	$I_{O(MAX)}$	V_{IN}-V_{OUT}=40V, P_D≦20W		0.2	0.3		A
RMS Noise vs. %of V_{OUT}	eN	10Hz≦f≦10KHz			0.003		%/V_{OUT}
Ripple Rejection	RR	V_{OUT}=10V,f=120Hz	C_{ADJ}=0		65		dB
			C_{ADJ}=10μF	66	80		

Note: C_{ADJ} is connected between Adjust pin and Ground.

APPLICATION CIRCUITS




Fig.1 Programmable voltage regulator

V_{OUT}= 1.25V*(1+R2/R1)+I_{ADJ}*R2

C1 is required when regulator is located an appreciated distance from power supply. Co is needed to improve transient response.




Fig.2 Regulator with On-off control





Fig.3 Soft Start Application



$I_{O(MAX)}=(\frac{V_{REF}}{R1})+I_{ADJ}=\frac{1.25V}{R1}$


$I_{O(MIN)}=(\frac{V_{REF}}{R1+R2})+I_{ADJ}=\frac{1.25V}{R1+R2}$

5mA<I_{OUT}<100mA


Fig.4 Constant Current Application

TYPICAL CHARACTERISTICS


Load Regulation vs. temperature




Adjustment Current vs. Temperature



Current Limit




Minimum Operating Current



PACKAGE INFORMATION


TO-220



Unit: mm

Symbol	Size		Symbol	Size		Symbol	Size		Symbol	Size	
	Min	Max		Min	Max		Min	Max		Min	Max
W	9.66	10.28	W5	9.80	10.20	L4**	6.20	6.60	T3	0.45	0.60
W1	2.54（TYP）		L	9.00	9.40	L5	2.79	3.30	G(Φ)	3.50	3.70
W2	0.70	0.95	L1	6.40	6.80	T	4.30	4.70			
W3	1.17	1.37	L2	2.70	2.90	T1	1.15	1.40			
W4*	1.32	1.72	L3	12.70	14.27	T2	2.20	2.60			

TO-220F




UNIT：mm


SYMBOL	min	nom	max	SYMBOL	min	nom	max
A	9.80		10.60	D		2.54	
A1		7.00		D1	1.15		1.55
A2	2.90		3.40	D2	0.60		1.00
A3	9.10		9.90	D3	0.20		0.50
B1	15.40		16.40	E	2.24		2.84
B2	4.35		4.95	E1		0.70	
B3	6.00		7.40	E2		1.0×45°	
C	3.00		3.70	E3	0.35		0.65
C1	15.00		17.00	E4	2.30		3.30
C2	8.80		10.80	α（度）		30°	

TO-263

Unit: mm




SOT-223



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.520	1.800	0.060	0.071
A1	0.000	0.100	0.000	0.004
A2	1.500	1.700	0.059	0.067
b	0.660	0.820	0.026	0.032
c	0.250	0.350	0.010	0.014
D	6.200	6.400	0.244	0.252
D1	2.900	3.100	0.114	0.122
E	3.300	3.700	0.130	0.146
E1	6.830	7.070	0.269	0.278
e	2.300(BSC)		0.091(BSC)	
e1	4.500	4.700	0.177	0.185
L	0.900	1.150	0.035	0.045
θ	0°	10°	0°	10°

TO-252



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	6.30	6.90	0.248	0.272
A1	0.00	0.16	0.000	0.006
B	5.70	6.30	0.224	0.248
C	2.10	2.50	0.083	0.098
D	0.30	0.70	0.012	0.028
E1	0.60	0.90	0.024	0.035
E2	0.70	1.00	0.028	0.039
F	0.30	0.60	0.012	0.024
G	0.70	1.20	0.028	0.047
L1	9.60	10.50	0.378	0.413
L2	2.70	3.10	0.106	0.122
H	0.40	1.00	0.016	0.039
M	5.10	5.50	0.201	0.217
N	2.09	2.49	0.082	0.098
R	0.30		0.012	
T	1.40	1.60	0.055	0.063
Y	5.10	6.30	0.201	0.248

TO-3




Fig.2 outline dimensions (unindicated tolerance:±0.1mm)

Revision History

Rev.	Change	Date
V1.0	Initial version	6/27/2021

Important Notice

JSMSEMI Semiconductor (JSMSEMI) PRODUCTS ARE NEITHER DESIGNED NOR INTENDED FOR USE IN MILITARY AND/OR AEROSPACE, AUTOMOTIVE OR MEDICAL DEVICES OR SYSTEMS UNLESS THE SPECIFIC JSMSEMI PRODUCTS ARE SPECIFICALLY DESIGNATED BY JSMSEMI FOR SUCH USE. BUYERS ACKNOWLEDGE AND AGREE THAT ANY SUCH USE OF JSMSEMI PRODUCTS WHICH JSMSEMI HAS NOT DESIGNATED FOR USE IN MILITARY AND/OR AEROSPACE, AUTOMOTIVE OR MEDICAL DEVICES OR SYSTEMS IS SOLELY AT THE BUYER’S RISK.

JSMSEMI assumes no liability for application assistance or customer product design. Customers are responsible for their products and applications using JSMSEMI products.

Resale of JSMSEMI products or services with statements diferent from or beyond the parameters stated by JSMSEMI for that product or service voids all express and any implied warranties for the associated JSMSEMI product or s ervice. JSMSEMI is not responsible or liable for any such statements.

JSMSEMI All Rights Reserved. Information and data in this document are owned by JSMSEMI wholly and may not be edited, reproduced, or redistributed in any way without the express written consent from JSMSEMI.

Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc.When designing equipment, refer to the "Delivery Specification" for the JSMSEMI product that you intend to use.

For additional information please contact Kevin@jsmsemi.com or visit www.jsmsemi.com