BORN SEMICONDUCTOR


BAT54WS

Schottky Barrier Diode

Features

- Low forward voltage drop
- High current capability
- High reliability
- High surge current capability
- Epitaxial construction


Package



Description

- Case: molded plastic
- Polarity: Color band denotes cathode
- Package: SOD-323 Plastic Package

Marking



Ordering information

Order code	Package	Marking	Base qty	Delivery mode
BAT54WS	SOD-323	S1	3K	Tape and reel

Maximum Ratings @T_A=25°C unless otherwise noted

Symbol	Parameter	Value	Unit
V_{RRM}	Maximum Repetitive Peak Reverse Voltage	30	V
V_{RMS}	Maximum RMS Voltage	21	V
V_{DC}	Maximum DC Blocking Voltage	30	V
I_{FM}	Maximum Average Forward Rectified Current	300	mA
I_{FSM}	Peak Forward Surge Current 8.3ms single half sine-wave	600	mA
P_D	Power Dissipation	200	mW
$R_{\theta JA}$	Typical Thermal Resistance	500	°C/W
T_J	Junction Temperature	125	°C
T_{STG}	Storage Temperature Range	-55 to +150	°C

BORN SEMICONDUCTOR , INC. ALL RIGHT RESERVED

Specifications are subject to change without notice.
Please refer to http://*www.born-tw.com* for current information.

Revision: 2022-Jan-1-A

BAT54WS

Schottky Barrier Diode

Electrical Characteristics @T_A=25°C unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V_R	Maximum Reverse Breakdown Voltage	I_R=100uA	30	–	–	V
V_F	Maximum Forward Voltage	I_F=0.1mA	–	–	240	mV
		I_F=1.0mA	–	–	320	mV
		I_F=10mA	–	–	400	mV
		I_F=30mA	–	–	500	mV
		I_F=100mA	–	–	1000	mV
I_R	Maximum Reverse Current	V_R=25V		–	2.0	uA
C_J	Type Junction Capacitance	V_R = 1V, f=1MHZ	–	–	10	pF
T_{rr}	Reverse Reverse Time	I_F = I_R=10mA V_R=6V	–	–	6	nS

BORN SEMICONDUCTOR , INC. ALL RIGHT RESERVED

Specifications are subject to change without notice.
Please refer to http://*www.born-tw.com* for current information.

BAT54WS

Schottky Barrier Diode

Typical Performance Characteristics(T_J = 25 °C, unless otherwise noted)

Figure 1: Forward Characteristics




Figure 2: Reverse Characteristics




Figure 3: Capacitance Characteristics





Figure 4: Power Derating Curve




BORN SEMICONDUCTOR , INC. ALL RIGHT RESERVED

Specifications are subject to change without notice.
Please refer to http://*www.born-tw.com* for current information.

BAT54WS


Schottky Barrier Diode

Outline Drawing - SOD-323




SYMBOL	MILLIMETER		INCHES	
	MIN.	MAX.	MIN.	MAX.
A	1.600	1.800	0.063	0.071
B	0.250	0.350	0.010	0.014
C	2.400	2.800	0.094	0.110
D	–	1.100	–	0.043
E	1.100	1.500	0.043	0.059
F	0.080	0.150	0.003	0.006
L	0.475REF		0.019REF	
L1	0.250	0.400	0.010	0.016
H	0.000	0.100	0.000	0.004

Packaging Tape - SOD-323



SYMBOL	MILLIMETER
A0	0.80±0.10
A1	1.48±0.10
B0	1.80±0.10
B1	3.00±0.10
d0	1.55±0.10
d1	1.00±0.05
E	1.75±0.10
F	3.50±0.10
K0	1.05±0.10
P	4.00±0.10
P0	4.00±0.10
P1	2.00±0.10
W	8.00±0.30
T	0.25 ±0.05

Packaging Reel



SYMBOL	MILLIMETER
A	177.8±0.2
B	2.7±0.2
C	13.5±0.2
D	9.6±0.3
E	54.5±0.2
F	12.3±0.3
T1	1.0±0.2
Quantity	3000PCS

BORN SEMICONDUCTOR , INC. ALL RIGHT RESERVED

Specifications are subject to change without notice.
Please refer to http://*www.born-tw.com* for current information.

Revision: 2022-Jan-1-A