TECH PUBLIC
台舟电子

TPM4015LS8G

N-CHANNEL ENHANCEMENT MODE MOSFET

WWW.TECHPUBLIC.COM

Product Summary

- V_{DS} 40 V
- I_{DS} (@ V_{GS}= 10V) 12A
- $R_{DS(ON)}$ (@ V_{GS}=10V) < 7mΩ(Typ)

Application

- LED applications
- Synchronous Rectifiers for SMPS
- Power management
- PWM Application

Package and Pin Configuration



SOP-8

Circuit diagram



Absolute Maximum Ratings (T_A=25℃unless otherwise noted)

PARAMETER		SYMBOL	LIMIT	UNIT
Drain-Source Voltage		V_{DS}	40	V
Gate-Source Voltage		V_{GS}	±20	V
Continuous Drain Current	T_A=25℃	I_D	12	A
Continuous Drain Current	T_A=100℃	I_D	8.5	A
Pulsed Drain Current (note1)		I_{DM}	36	A
Single Pulse Avalanche Energy L=8.7mH，IAS=6A		EAS	76	mJ
Maximum Power Dissipation T_A=25℃		P_D	1.47	W
Operating Junction Temperature Range		T_J	-55 to +150	℃
Storage Temperature Range		T_{stg}	-55 to +150	℃

Thermal Characteristic

PARAMETER		Symbol	Value	Unit
Thermal Resistance Junction-ambient	PCB Mount (note2)	$R_{\theta JA}$	62.5	°C/W
Thermal Resistance Junction-Case		$R_{\theta JC}$	28	°C/W

notes 1. Repetitive Rating: Pulse width limited by maximum junction temperature.

2 . When mounted on 1" square PCB (FR4 material).

Electrical Characteristics (T_A=25℃unless otherwise noted)

PARAMETER	CONDITIONS	SYMBOL	MIN	TYP	MAX	UNIT
Static						
Drain-Source Breakdown Voltage	V_{GS}=0V, I_D=250μA	BV_{DSS}	40	--	--	V
Gate-Source Threshold Voltage	V_{DS}=V_{GS} , I_D= 250μA	$V_{GS(th)}$	1.2	1.8	2.5	V
Gate-Source Leakage	V_{DS}=0V, V_{GS}= ±20V	I_{GSS}	--	--	±100	nA
Zero Gate Voltage Drain Current	V_{DS}= 40V, V_{GS}=0V	I_{DSS}	--	--	1	μA
	V_{DS}= 32V, T_J=85°C		--	--	10	μA
Drain-Source On-State Resistance (Note 1)	V_{GS}= 10V, I_D=8A	R_{DS}(on)	--	7	12	mΩ
	V_{GS}= 4.5V, I_D=4A		--	12	15	mΩ
Forward Transconductance (Note 2)	V_{DS}= 10V, I_D= 10A	g_{fs}	--	14	--	S
Dynamic (Note 2)						
Total Gate Charge (Note 3)	V_{DS} = 20V, I_D =8A, V_{GS} =10V	Q_g	--	12	--	nC
Gate-Source Charge (Note 3)		Q_{gs}	--	3.3	--	
Gate-Drain Charge (Note 3)		Q_{gd}	--	6.7	--	
Input Capacitance	V_{DS} =25V, V_{GS} = 0V, F= 1.0MHz	C_{iss}	--	1220	--	pF
Output Capacitance		C_{oss}	--	120	--	
Reverse Transfer Capacitance		C_{rss}	--	55	--	
Switching						
Turn-On Delay Time (Note 3)	V_{DD} = 20V, I_D= 10A, V_{GS} = 10V, R_G = 3.3Ω	$t_{d(on)}$	--	13	--	nS
Rise Time (Note 3)		t_r	--	2.2	--	
Turn-Off Delay Time (Note 3)		$t_{d(off)}$	--	72	--	
Fall Time (Note 3)		t_f	--	4.5	--	
Source-Drain Diode Ratings and Characteristics (Note 2)						
Forward Voltage	V_{GS} = 0V, I_{SD} = 2A	V_{SD}	--	0.7	1.1	V
Continuous Source Current	Integral reverse diode in the MOSFET	I_S	--	--	12	A
Pulsed Current (Note 1)		I_{SM}	--	--	36	A

Notes:

1. Pulse test; pulse width ≤ 300 μS, duty cycle ≤ 2%.
2. Guaranteed by design, not subject to production testing.
3. Independent of operating temperature

TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)



Fig.1 Continuous Drain Current vs. T_C



Fig.2 Normalized RDSON vs. T_J



Fig.3 Normalized V_{th} vs. T_J



Fig.4 Gate Charge Waveform



Fig.5 Normalized Transient Impedance



Fig.6 Maximum Safe Operation Area

Package Information

SOP-8



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	1.350	1.750	0.053	0.069
A1	0.100	0.250	0.004	0.010
A2	1.350	1.550	0.053	0.061
b	0.330	0.510	0.013	0.020
c	0.170	0.250	0.006	0.010
D	4.700	5.100	0.185	0.200
E	3.800	4.000	0.150	0.157
E1	5.800	6.200	0.228	0.244
e	1.270(BSC)		0.050(BSC)	
L	0.400	1.270	0.016	0.050
θ	0°	8°	0°	8°