
Features


- 20V, 0.75A
  $R_{DS(ON)}$< 165mΩ @ V_{GS} =4.5V
  $R_{DS(ON)}$< 200mΩ @ V_{GS} =2.5V
- Advanced Trench Technology
- Excellent $R_{DS(ON)}$ and Low Gate Charge
- Lead free product is acquired
- ESD Protected: 2KV




SOT-723-3L top view

Application

- Load Switch
- PWM Application
- Power management



Pin Assignment



Schematic Diagram

Absolute Maximum Ratings (T_A=25℃ unless otherwise specified)

Symbol	Parameter		Max.	Units
V_{DSS}	Drain-Source Voltage		20	V
V_{GSS}	Gate-Source Voltage		±10	V
I_D	Continuous Drain Current	T_A= 25℃	0.75	A
		T_A= 100℃	0.5	A
I_{DM}	Pulsed Drain Current note1		3	A
P_D	Power Dissipation	T_A= 25℃	0.15	W
$R_{\theta JA}$	Thermal Resistance, Junction to Case		833	℃/W
T_J, T_{STG}	Operating and Storage Temperature Range		-55 to +150	℃

Electrical Characteristics (T_J=25℃ unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Units
Off Characteristic						
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	V_{GS}=0V, I_D=250μA	20	-	-	V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=20V, V_{GS}=0V,	-	-	1	μA
I_{GSS}	Gate to Body Leakage Current	V_{DS}=0V, V_{GS}= ±10V	-	-	±10	uA
On Characteristics						
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS}, I_D=250μA	0.4	0.7	1.0	V
$R_{DS(on)}$	Static Drain-Source on-Resistance note2	V_{GS}=4.5V, I_D=0.5A	-	100	165	mΩ
		V_{GS}=2.5V, I_D=0.4A	-	150	200	
Dynamic Characteristics						
C_{iss}	Input Capacitance	V_{DS}=10V, V_{GS}=0V, f=1.0MHz	-	24	-	pF
C_{oss}	Output Capacitance		-	13	-	pF
C_{rss}	Reverse Transfer Capacitance		-	10	-	pF
Q_g	Total Gate Charge	V_{DS}=10V, I_D=0.75A, V_{GS}=4.5V	-	1	-	nC
Q_{gs}	Gate-Source Charge		-	0.28	-	nC
Q_{gd}	Gate-Drain(“Miller”) Charge		-	0.22	-	nC
Switching Characteristics						
$t_{d(on)}$	Turn-on Delay Time	V_{DS}=10V, I_D=0.5A, R_{GEN}=10Ω, V_{GS}=4.5V	-	2	-	ns
t_r	Turn-on Rise Time		-	19	-	ns
$t_{d(off)}$	Turn-off Delay Time		-	10	-	ns
t_f	Turn-off Fall Time		-	23	-	ns
Drain-Source Diode Characteristics and Maximum Ratings						
I_S	Maximum Continuous Drain to Source Diode Forward Current		-	-	0.75	A
I_{SM}	Maximum Pulsed Drain to Source Diode Forward Current		-	-	3	A
V_{SD}	Drain to Source Diode Forward Voltage	V_{GS}=0V, I_S=0.75A	-	-	1.2	V

Notes:1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature

2. Pulse Test: Pulse Width≤300μs, Duty Cycle≤0.5%

Typical Performance Characteristics

Figure1: Output Characteristics




Figure 2: Typical Transfer Characteristics




Figure 3: On-resistance vs. Drain Current




Figure 4: Body Diode Characteristics




Figure 5: Gate Charge Characteristics




Figure 6: Capacitance Characteristics




Figure 7: Normalized Breakdown Voltage vs. Junction Temperature




Figure 8: Normalized on Resistance vs. Junction Temperature




Figure 9: Maximum Safe Operating Area




Figure 10: Maximum Continuous Drain Current vs. Ambient Temperature





Figure.11: Maximum Effective Transient Thermal Impedance, Junction-to-Ambient



Test Circuit




Figure1:Gate Charge Test Circuit & Waveform




Figure 2: Resistive Switching Test Circuit & Waveforms







Figure 3:Unclamped Inductive Switching Test Circuit & Waveforms

Package Mechanical Data-SOT-723-3L







COMMON DIMENSION (MM)			
PKG	SOT-723-3L		
SYMBOL	MIN	NOM	MAX
A	0.420	0.450	0.480
A1	0.100	0.110	0.120
b	0.230	0.250	0.280
c	0.180	0.200	0.235
D	1.150	1.200	1.300
E	0.750	0.800	0.850
L	1.170	1.200	1.240
e	0.750	0.800	0.850
Q		8°	