
■ DESCRIPTION


The MBR20200CS meet the ROHS and Green Product requirement with full function reliability approved.



■ FEATURE

* Schottky Barrier Chip
* Guard Ring Die Construction for Transient Protection
* Low Power Loss,High Efficiency
* High Surge Capability
* High Current Capability and Low Forward Voltage Drop
* For Use in Low Voltage, High Frequency Inverters,Free Wheeling, and Polarity Protection Applications

1. ANODE
2. CATHODE
3. ANODE



■ ABSOLUTE MAXIMUM RATINGS(TA=25°C, unless otherwise specified.)

SYMBOL	PARAMETER		VALUE	UNIT
VRRM	Peak repetitive reverse voltage		200	V
VRWM	Working peak reverse voltage		200	V
VR	DC blocking voltage		200	V
VR(RMS)	RMS reverse voltage		140	V
IO	Average rectified output current		20（10*2）	A
IFSM	Non-Repetitive peak forward surge current(8.3ms half sine wave)		150*2	A
Tj	Junction temperature		175	°C
Tstg	Storage temperature		-55 ~ +150	°C
Cj (Ctot)	Typical total capacitance VR=5V,f=1MHz		500	pF
RθJA	Thermal Resistance fromJunction to Ambient	TO-252	100	°C/W
		TO-220F	58	
RθJC	Thermal Resistance From Junction To Case	TO-252	5	°C/W
		TO-220F	3	

Notes:Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ ELECTRICAL CHARACTERISTICS (TA=25°C, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS		MIN	TYP	MAX	UNIT
Reverse voltage	V(BR)	I R=0.2mA		200			V
Reverse current	IR	VR=200V	Tj =25℃			100	uA
			Tj =125℃		2.0		mA
Forward voltage	VF	IF=5A	Tj =25℃		0.82	0.85	V
			Tj =125℃		0.66		V
		IF=10A	Tj =25℃		0.87	0.90	V
			Tj =125℃		0.74		V
Pulse test: pulse width ≤300μs, duty cycle≤ 2.0%.							

■ TYPICAL CHARACTERISTICS

FIG.1: FORWARD CURRENT DERATING CURVE




FIG.2: TYPICAL FORWARD CHARACTERISTICS




FIG.3: TOTAL CAPACITANCE DERATING CURVE







FIG.4: TYPICAL REVERSE CHARACTERISTICS



■ TO - 252 Package Outline Dimensions





■ TO - 252 Packing Information

Package version	Reel dimensions Φ×H (mm)	Per Reel (pcs)	Reels per box	Inner box dimensions L×W×H(mm)	Outer box (pcs)	Outer box dimensions L×W×H (mm)
TO-252	Φ330*20	2500	2	360*340*50	25000	375*375*280