







SECTION A–A
SCALE 1:1


Note:
1. Material:
 1.1 Housing: thermoplastic high temp.UL94V–0; Color: natural.
 1.2 Latch: thermoplastic high temp.UL94V–0; Color: black.
 1.3 Terminal: copper alloy.
 1.4 Fitting Nail: copper alloy.
2. Finsh:
 2.1 Terminal:
  Underplating: Au/matt Tin overall.
 2.2 Fitting Nail:
  Underplating: matt Tin overall.
3. Product must comply HF RoHS specification.
4. Product No:

5001 — FCS 05 20 — ** R 1-00 -B
- Standby
- ALTERNATE
- PACKING:R:卷;T:管
- PIN
- HIGH:2.0
- PITCH:0.5
- 抽屉上接
- JME CONNECTOR SERIES


CKTS	DIM A	DIM B	DIM C	DIM D	DIM E	DIM F
4	1.50	2.60	6.50	7.60		
5	2.00	3.10	7.00	8.10		
6	2.50	3.60	7.50	8.60		
7	3.00	4.10	8.00	9.10		
8	3.50	4.60	8.50	9.60		
9	4.00	5.10	9.00	10.10		
10	4.50	5.60	9.50	10.60		
11	5.00	6.10	10.00	11.10		
12	5.50	6.60	10.50	11.60		
13	6.00	7.10	11.00	12.10		
14	6.50	7.60	11.50	12.60		
15	7.00	8.10	12.00	13.10		
16	7.50	8.60	12.50	13.60		
17	8.00	9.10	13.00	14.10		
18	8.50	9.60	13.50	14.60		
19	9.00	10.10	14.00	15.10	5.20	6.45
20	9.50	10.60	14.50	15.60		
21	10.00	11.10	15.00	16.10		
22	10.50	11.60	15.50	16.60		
23	11.00	12.10	16.00	17.10		
24	11.50	12.60	16.50	17.60		
25	12.00	13.10	17.00	18.10		
26	12.50	13.60	17.50	18.60		
27	13.00	14.10	18.00	19.10		
28	13.50	14.60	18.50	19.60		
29	14.00	15.10	19.00	20.10		
30	14.50	15.60	19.50	20.60		
31	15.00	16.10	20.00	21.10		
32	15.50	16.60	20.50	21.60		
33	16.00	17.10	21.00	22.10		
34	16.50	17.60	21.50	22.60		
35	17.00	18.10	22.00	23.10		
36	17.50	18.60	22.50	23.60		
37	18.00	19.10	23.00	24.10		
38	18.50	19.60	23.50	24.60		
39	19.00	20.10	24.00	25.10		
40	19.50	20.60	24.50	25.60		
41	20.00	21.10	25.00	26.10		
42	20.50	21.60	25.50	26.60		
43	21.00	22.10	26.00	27.10		
44	21.50	22.60	26.50	27.60		
45	22.00	23.10	27.00	28.10		
46	22.50	23.60	27.50	28.60		
47	23.00	24.10	28.00	29.10	5.75	7.00
48	23.50	24.60	28.50	29.60		
49	24.00	25.10	29.00	30.10		
50	24.50	25.60	29.50	30.60		
51	25.00	26.10	30.00	31.10		
52	25.50	26.60	30.50	31.60		
53	26.00	27.10	31.00	32.10		
54	26.50	27.60	31.50	32.60		
55	27.00	28.10	32.00	33.10		
56	27.50	28.60	32.50	33.60		
57	28.00	29.10	33.00	34.10		
58	28.50	29.60	33.50	34.60		
59	29.00	30.10	34.00	35.10		
60	29.50	30.60	34.50	35.60		







RECOMMENDED P.C.B PATTERN LAYOUT



RECOMMENDED FPC/FFC DIMENSION

Rev 版本	Change Description 变更内容	Date 日期	Revisor 制/修订人
A	初版发行	2011/09/16	Allan

CUSTOMER DRAWING

Tolerance Unspecified (未注公差) 0.0 ±0.15 0°. ±5° 0.00 ±0.10 0°.0 ±3° 0.000 ±0.05 0°.00 ±1°	Size(图幅): A4
	Unit(单位): MM
	Scale(比例): 1 : 1
Project View (投影视角)	Page(页数): 1 OF 1
	Rev(版本): A

深圳市文章济美科技有限公司
Shenzhen WenZhangJiMei technology co., LTD

Product Name(产品名称): 0.5Pitch H=2.0 FPC ZIF R/A Upper Type3 SMT CONN		
Product No(产品料号): 5001-FCS0520-**R1-00-B		
Designer(设计): Allan 09/16'11	Checked(审核):	Approved(核准):