BORN SEMICONDUCTOR


# BN5A121V50

**ESD Protection Diode**

## Features

- 1600Watts peak pulse power (tp = 8/20μs)
- Unidirectional configurations
- Solid-state silicon-avalanche technology
- Low clamping Voltage
- Low leakage current
- Protection one data/power line
- IEC 61000-4-2 ±30kV contact ; ±30kV air
- IEC 61000-4-4 (EFT) 40A (5/50ns)
- IEC 61000-4-5 (Lightning) 65A (8/20μs)

## Package





## Applications

- Cell Phone Handsets and Accessories
- Microprocessor based equipment
- Personal Digital Assistants (PDA's)
- Notebooks, Desktops, and Servers
- Portable Instrumentation

## Mechanical Characteristics

- DFN1610-2L package
- Molding compound flammability rating: UL 94V-0
- Packaging: Tape and Reel
- RoHS/WEEE Compliant

## Marking




## Ordering information

| Order code | Package | Base qty | Delivery mode |
|---|---|---|---|
| BN5A121V50 | DFN1610-2L | 10k | Tape and reel |

*BORN SEMICONDUCTOR , INC. ALL RIGHT RESERVED*

Specifications are subject to change without notice.
Please refer to http://*www.born-tw.com* for current information.


**Revision: 2022-Jan-1-A**

# BN5A121V50

**ESD Protection Diode**

## Electrical Parameters ($T_A$ = 25°C unless otherwise noted)

| Symbol | Parameter |
|---|---|
| $I_{PP}$ | Maximum Reverse Peak Pulse Current |
| $V_C$ | Clamping Voltage @ $I_{PP}$ |
| $V_{RWM}$ | Peak Reverse Working Voltage |
| $I_R$ | Reverse Leakage Current @ $V_{RWM}$ |
| $V_{BR}$ | Breakdown Voltage @ $I_T$ |
| $I_T$ | Test Current |
| | |
| | |




Note:8/20us pulse Waveform.

## Absolute Maximum Rating

| Rating | Symber | Value | Units |
|---|---|---|---|
| Peak Pulse Power ( tp =8/20μs ) | $P_{PP}$ | 1600 | Watts |
| Peak Pulse Current (tp =8/20μs ) | $I_{PP}$ | 65 | A |
| ESD per IEC 61000-4-2 (Air)<br>ESD per IEC 61000-4-2 (Contact) | $V_{ESD}$ | 30<br>30 | KV |
| Lead Soldering Temperature | $T_L$ | 260(10seconds) | °C |
| Junction Temperature | $T_J$ | -55 to + 150 | °C |
| Storage Temperature | $T_{stg}$ | -55 to + 150 | °C |

## Electrical Characteristics

| Parameter | Symber | Conditions | Min | Typical | Max | Units |
|---|---|---|---|---|---|---|
| Reverse Stand-Off Voltage | $V_{RWM}$ | – | – | – | 12 | V |
| Reverse Breakdown Voltage | $V_{BR}$ | $I_T$=1mA | 13.3 | – | 17.0 | V |
| Reverse Leakage Current | $I_R$ | $V_{RWM}$=12V,T=25°C | – | 0.1 | 0.5 | uA |
| Peak Pulse Current | $I_{PP}$ | tp =8/20us | – | – | 65 | A |
| Clamping Voltage | $V_C$ | $I_{PP}$=65A, tp =8/20us | – | 20 | 25 | V |
| Junction Capacitance | $C_j$ | $V_R$=0V,T=25°C,f=1MHZ | – | 450 | 500 | pF |

*BORN SEMICONDUCTOR , INC. ALL RIGHT RESERVED*


Specifications are subject to change without notice.
Please refer to http://*www.born-tw.com* for current information.

# BN5A121V50


ESD Protection Diode

## Typical Characteristics


### Figure 1: Peak Pulse Power vs. Pulse Time





### Figure 2: Power Derating Curve




### Figure 3: Pulse Waveform




### Figure 4: Clamping Voltage vs. $I_{PP}$





BORN SEMICONDUCTOR , INC. ALL RIGHT RESERVED

Specifications are subject to change without notice.
Please refer to http://www.born-tw.com for current information.

# BN5A121V50


**ESD Protection Diode**

## Outline Drawing – DFN1610-2L





| SYMBOL | MILLIMETER | | |
|---|---|---|---|
| | MIN. | Typ. | MAX. |
| A | 0.45 | 0.50 | 0.55 |
| A1 | – | 0.02 | 0.05 |
| A2 | 0.119 | 0.127 | 0.135 |
| E | 1.55 | 1.60 | 1.65 |
| D | 0.95 | 1.00 | 1.05 |
| b | – | 0.80 | – |
| e | 1.1039BSC | | |
| L | 0.35 | 0.40 | 0.45 |
| L1 | 0.05REF | | |

## Packaging Tape - DFN1610




| SYMBOL | MILLIMETER |
|---|---|
| A0 | 1.11±0.05 |
| B0 | 1.72±0.05 |
| d0 | $1.5^{+0.1}_{-0}$ |
| d1 | 0.50±0.1 |
| E | 1.75±0.10 |
| F | 3.50±0.05 |
| K0 | 0.68±0.05 |
| P | 2.00±0.1 |
| P0 | 4.00±0.10 |
| P1 | 2.00±0.05 |
| W | $8.00^{+0.03}_{-0.01}$ |
| T | 0.25±0.05 |

## Packaging Reel




| SYMBOL | MILLIMETER |
|---|---|
| A | 178±1 |
| B | 3.5±0.2 |
| C | 14.3±0.2 |
| D | $9.8^{+2}_{-1}$ |
| E | 54.5±0.5 |
| F | 12.4±0.5 |
| T1 | 1.0±0.2 |
| Quantity | 10000PCS |

*BORN SEMICONDUCTOR , INC. ALL RIGHT RESERVED*

Specifications are subject to change without notice.
Please refer to http://*www.born-tw.com* for current information.

**Revision: 2022-Jan-1-A**