SI7403BDN-T1-GE3-VB Datasheet

P-Channel 12 V (G-S) MOSFET

PRODUCT SUMMARY			
V_{DS} (V)	$R_{DS(on)}$ (Ω)	I_D (A)[a]	Q_g (Typ.)
- 12	0.015 at V_{GS} = - 4.5 V	- 25	35 nC
	0.021 at V_{GS} = - 2.5 V	- 24	
	0.023 at V_{GS} = - 1.8 V	- 24	

FEATURES

- **Halogen-free according to IEC 61249-2-21 Definition**
- TrenchFET® Power MOSFET
- Ultra Small DFN3x3 Chipscale Packaging Reduces Footprint Area, Profile (0.62 mm) and On-Resistance Per Footprint Area
- **Compliant to RoHS Directive 2002/95/EC**

Pb-free
RoHS COMPLIANT

APPLICATIONS

- PA Switch
- Battery Switch
- Load Switch

Pin Description

Top View Bottom View



DFN3x3-8(punch type)

Top View





P-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS (T_A = 25 °C, unless otherwise noted)				
Parameter		**Symbol**	**Limit**	**Unit**
Drain-Source Voltage		V_{DS}	- 12	V
Gate-Source Voltage		V_{GS}	± 8	
Continuous Drain Current (T_J = 150 °C)	T_C = 25 °C	I_D	- 25	A
	T_C = 70 °C		- 19	
	T_A = 25 °C		- 20[b, c]	
	T_A = 70 °C		- 11[b, c]	
Pulsed Drain Current		I_{DM}	- 80	
Continuous Source-Drain Diode Current	T_C = 25 °C	I_S	- 26.7	
	T_A = 25 °C		- 3.5[b, c]	
Maximum Power Dissipation	T_C = 25 °C	P_D	37	W
	T_C = 70 °C		26	
	T_A = 25 °C		3.9[b, c]	
	T_A = 70 °C		1.96[b, c]	
Operating Junction and Storage Temperature Range		T_J, T_{stg}	- 55 to 150	°C
Package Reflow Conditions[d]	IR/Convection		260	

Notes:
a. Based on T_C = 25 °C.
b. Surface mounted on 1" x 1" FR4 board.
c. t = 10 s.
d. Refer to IPC/JEDEC (J-STD-020), no manual or hand soldering.
e. In this document, any reference to the *Case* represents the body of the DFN2X2 device and *Foot* is the bump.

THERMAL RESISTANCE RATINGS					
Parameter		**Symbol**	**Typical**	**Maximum**	**Unit**
Maximum Junction-to-Ambient[a, b]		R_{thJA}	31	42	°C/W
Maximum Junction-to-Foot (Drain)	Steady State	R_{thJF}	13	16	

Notes:
a. Surface mounted on 1" x 1" FR4 board.
b. Maximum under steady state conditions is 72 °C/W.

SPECIFICATIONS (T_J = 25 °C, unless otherwise noted)						
Parameter	**Symbol**	**Test Conditions**	**Min.**	**Typ.**	**Max.**	**Unit**
Static						
Drain-Source Breakdown Voltage	V_{DS}	V_{GS} = 0 V, I_D = - 250 µA	- 12			V
V_{DS} Temperature Coefficient	$\Delta V_{DS}/T_J$	I_D = - 250 µA		- 13.3		mV/°C
$V_{GS(th)}$ Temperature Coefficient	$\Delta V_{GS(th)}/T_J$			2.4		
Gate-Source Threshold Voltage	$V_{GS(th)}$	V_{DS} = V_{GS}, I_D = - 250 µA	- 0.5		- 1.5	V
Gate-Source Leakage	I_{GSS}	V_{DS} = 0 V, V_{GS} = 5 V			- 100	nA
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = - 12 V, V_{GS} = 0 V			- 1	µA
		V_{DS} = - 12 V, V_{GS} = 0 V, T_J = 70 °C			- 10	
On-State Drain Current[a]	$I_{D(on)}$	$V_{DS} \leq$ 5 V, V_{GS} = - 4.5 V	- 20			A
Drain-Source On-State Resistance[a]	$R_{DS(on)}$	V_{GS} = - 4.5 V, I_D = - 1 A		0.015		Ω
		V_{GS} = - 2.5 V, I_D = - 1 A		0.021		
		V_{GS} = - 1.8 V, I_D = - 1 A		0.023		
Forward Transconductance[a]	g_{fs}	V_{DS} = - 4 V, I_D = - 1 A		8.3		S
Dynamic[b]						
Input Capacitance	C_{iss}	V_{DS} = - 6 V, V_{GS} = 0 V, f = 1 MHz		2220		pF
Output Capacitance	C_{oss}			865		
Reverse Transfer Capacitance	C_{rss}			555		
Total Gate Charge	Q_g	V_{DS} = - 6 V, V_{GS} = - 5 V, I_D = - 1 A		38	57	nC
		V_{DS} = - 6 V, V_{GS} = - 4.5 V, I_D = - 1 A		35	53	
Gate-Source Charge	Q_{gs}			7.3		
Gate-Drain Charge	Q_{gd}			5.9		
Gate Resistance	R_g	V_{GS} = - 0.1 V, f = 1 MHz		28		Ω
Turn-On Delay Time	$t_{d(on)}$	V_{DD} = - 6 V, R_L = 4 Ω $I_D \cong$ - 1 A, V_{GEN} = - 4.5 V, R_g = 6 Ω		14	21	ns
Rise Time	t_r			25	40	
Turn-Off Delay Time	$t_{d(off)}$			380	570	
Fall Time	t_f			240	360	

SPECIFICATIONS T_J = 25 °C, unless otherwise noted						
Parameter	**Symbol**	**Test Conditions**	**Min.**	**Typ.**	**Max.**	**Unit**
Drain-Source Body Diode Characteristics						
Continuous Source-Drain Diode Current	I_S	T_C = 25 °C		- 8		A
Pulse Diode Forward Current	I_{SM}			- 25		
Body Diode Voltage	V_{SD}	I_S = - 1 A, V_{GS} = 0 V		- 0.65	- 1.2	V
Body Diode Reverse Recovery Time	t_{rr}	I_F = - 1 A, dI/dt = 100 A/µs, T_J = 25 °C		311	467	ns
Body Diode Reverse Recovery Charge	Q_{rr}			1.136	1.705	µC
Reverse Recovery Fall Time	t_a			116		ns
Reverse Recovery Rise Time	t_b			195		

Notes:
a. Pulse test; pulse width ≤ 300 µs, duty cycle ≤ 2 %.
b. Guaranteed by design, not subject to production testing.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)



Output Characteristics



Transfer Characteristics



On-Resistance vs. Drain Current and Gate Voltage



Capacitance



Gate Charge



On-Resistance vs. Junction Temperature

TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)



Source-Drain Diode Forward Voltage



On-Resistance vs. Gate-to-Source Voltage



Threshold Voltage



Single Pulse Power, Junction-to-Ambient



* V_{GS} > minimum V_{GS} at which $R_{DS(on)}$ is specified

Safe Operating Area, Junction-to-Ambient

TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)



Current Derating*



Power Derating



Normalized Thermal Transient Impedance, Junction-to-Ambient



Normalized Thermal Transient Impedance, Junction-to-Foot

DFN3x3A_8L_NEP_P PACKAGE OUTLINE



RECOMMENDED LAND PATTERN



UNIT: mm

SYMBOLS	DIMENSIONS IN MILLIMETERS			DIMENSIONS IN INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	0.70	0.80	0.90	0.028	0.031	0.035
A1	0.00	—	0.05	0.000	—	0.002
b	0.24	0.30	0.35	0.009	0.012	0.014
c	0.08	0.15	0.25	0.003	0.006	0.010
D	2.80	2.90	3.00	0.110	0.114	0.118
E	2.70	2.80	2.90	0.106	0.110	0.114
E1	2.20	2.30	2.40	0.0087	0.091	0.095
e	0.65 BSC			0.026 BSC		
L	0.20	0.38	0.45	0.008	0.015	0.018
L1	0.05	---	0.10	0.002	---	0.004
θ1	0°	10°	12°	0°	10°	12°

NOTE
1. PAKCAGE BODY SIZES EXCLUDE MOLD FLASH AND GATE BURRS.
   MOLD FLASH AT THE NON-LEAD SIDES SHOULD BE LESS THAN 6 MIL EACH.
2. CONTROLLING DIMENSION IS MILLIMETER.
   CONVERTED INCH DIMENSIONS ARE NOT NECESSARILY EXACT.

Disclaimer

All products due to improve reliability, function or design or for other reasons, product specifications and data are subject to change without notice.

Taiwan VBsemi Electronics Co., Ltd., branches, agents, employees, and all persons acting on its or their representatives (collectively, the "Taiwan VBsemi"), assumes no responsibility for any errors, inaccuracies or incomplete data contained in the table or any other any disclosure of any information related to the product.(www.VBsemi.com)

Taiwan VBsemi makes no guarantee, representation or warranty on the product for any particular purpose of any goods or continuous production. To the maximum extent permitted by applicable law on Taiwan VBsemi relinquished: (1) any application and all liability arising out of or use of any products; (2) any and all liability, including but not limited to special, consequential damages or incidental ; (3) any and all implied warranties, including a particular purpose, non-infringement and merchantability guarantee.

Statement on certain types of applications are based on knowledge of the product is often used in a typical application of the general product VBsemi Taiwan demand that the Taiwan VBsemi of. Statement on whether the product is suitable for a particular application is non-binding. It is the customer's responsibility to verify specific product features in the products described in the specification is appropriate for use in a particular application. Parameter data sheets and technical specifications can be provided may vary depending on the application and performance over time. All operating parameters, including typical parameters must be made by customer's technical experts validated for each customer application. Product specifications do not expand or modify Taiwan VBsemi purchasing terms and conditions, including but not limited to warranty herein.

Unless expressly stated in writing, Taiwan VBsemi products are not intended for use in medical, life saving, or life sustaining applications or any other application. Wherein VBsemi product failure could lead to personal injury or death, use or sale of products used in Taiwan VBsemi such applications using client did not express their own risk. Contact your authorized Taiwan VBsemi people who are related to product design applications and other terms and conditions in writing.

The information provided in this document and the company's products without a license, express or implied, by estoppel or otherwise, to any intellectual property rights granted to the VBsemi act or document. Product names and trademarks referred to herein are trademarks of their respective representatives will be all.

Material Category Policy

Taiwan VBsemi Electronics Co., Ltd., hereby certify that all of the products are determined to be RoHS compliant and meets the definition of restrictions under Directive of the European Parliament 2011/65 / EU, 2011 Nian. 6. 8 Ri Yue restrict the use of certain hazardous substances in electrical and electronic equipment (EEE) - modification, unless otherwise specified as inconsistent.(www.VBsemi.com)

Please note that some documents may still refer to Taiwan VBsemi RoHS Directive 2002/95 / EC. We confirm that all products identified as consistent with the Directive 2002/95 / EC European Directive 2011/65 /.

Taiwan VBsemi Electronics Co., Ltd. hereby certify that all of its products comply identified as halogen-free halogen-free standards required by the JEDEC JS709A. Please note that some Taiwanese VBsemi documents still refer to the definition of IEC 61249-2-21, and we are sure that all products conform to confirm compliance with IEC 61249-2-21 standard level JS709A.