BORN SEMICONDUCTOR


BN5A201V

ESD Protection Diode

Features

- 3200Watts peak pulse power (tp = 8/20μs)
- Unidirectional configurations
- Solid-state silicon-avalanche technology
- Low clamping Voltage
- Low leakage current
- Complies with following standards:
- IEC 61000-4-2 (ESD) immunity test
- Air discharge: ±30KV ;Contact discharge: ±30KV
- IEC 61000-4-4 (EFT) 40A (5/50ns)
- IEC 61000-4-5 (Lightning) 80A (8/20μs)

Package




Applications

- Computer
- Microprocessor based equipment
- Personal Digital Assistants (PDA's)
- Digital Cameras
- Personal Digital Assistants

Mechanical Characteristics

- DFN1610-2L package
- Molding compound flammability rating: UL 94V-0
- Packaging: Tape and Reel
- RoHS/WEEE Compliant

Marking



Ordering information

Order code	Package	Base qty	Delivery mode
BN5A201V	DFN1610-2L	10k	Tape and reel

BORN SEMICONDUCTOR , INC. ALL RIGHT RESERVED


Specifications are subject to change without notice.
Please refer to http://*www.born-tw.com* for current information.

BN5A201V

ESD Protection Diode

Electrical Parameters (T_A = 25°C unless otherwise noted)

Symbol	Parameter
I_{PP}	Maximum Reverse Peak Pulse Current
V_C	Clamping Voltage @ I_{PP}
V_{RWM}	Peak Reverse Working Voltage
I_R	Reverse Leakage Current @ V_{RWM}
V_{BR}	Breakdown Voltage @ I_T
I_T	Test Current



Note:8/20us pulse Waveform.

Absolute Maximum Rating

Rating	Symber	Value	Units
Peak Pulse Power (tp =8/20μs)	P_{PP}	3200	Watts
Peak Pulse Current (tp =8/20μs)	I_{PP}	80	A
ESD per IEC 61000-4-2 (Air) ESD per IEC 61000-4-2 (Contact)	V_{ESD}	30 30	KV
Lead Soldering Temperature	T_L	260(10seconds)	°C
Junction Temperature	T_J	-55 to + 150	°C
Storage Temperature	T_{stg}	-55 to + 150	°C

Electrical Characteristics

Parameter	Symber	Conditions	Min	Typical	Max	Units
Reverse Stand-Off Voltage	V_{RWM}	–	–	–	20.0	V
Reverse Breakdown Voltage	V_{BR}	I_T=1mA	22	25	27	V
Reverse Leakage Current	I_R	V_{RWM}=20V,T=25°C	–	–	1	uA
Peak Pulse Current	I_{PP}	tp =8/20us	–	–	80	A
Clamping Voltage	V_C	I_{PP}=80A, tp =8/20us	–	38	40	V
Junction Capacitance	C_j	V_R=0V,T=25°C,f=1MHZ	–	200	–	pF

BORN SEMICONDUCTOR , INC. ALL RIGHT RESERVED

Specifications are subject to change without notice.
Please refer to http://*www.born-tw.com* for current information.

BN5A201V

ESD Protection Diode

Typical Characteristics

Figure 1: Peak Pulse Power vs. Pulse Time




Figure 2: Power Derating Curve




Figure 3: Pulse Waveform





Figure 4: Clamping Voltage vs. I_{PP}




BORN SEMICONDUCTOR , INC. ALL RIGHT RESERVED

Specifications are subject to change without notice.
Please refer to http://*www.born-tw.com* for current information.

BN5A201V


ESD Protection Diode

Outline Drawing – DFN1610-2L




SYMBOL	MILLIMETER		
	MIN.	Typ.	MAX.
A	0.45	0.50	0.55
A1	–	0.02	0.05
A2	0.119	0.127	0.135
E	1.55	1.60	1.65
D	0.95	1.00	1.05
b	–	0.80	–
e	1.1039BSC		
L	0.35	0.40	0.45
L1	0.05REF		

Packaging Tape - DFN1610



SYMBOL	MILLIMETER
A0	1.11±0.05
B0	1.72±0.05
d0	$1.5^{+0.1}_{-0}$
d1	0.50±0.1
E	1.75±0.10
F	3.50±0.05
K0	0.68±0.05
P	2.00±0.1
P0	4.00±0.10
P1	2.00±0.05
W	$8.00^{+0.03}_{-0.01}$
T	0.25±0.05

Packaging Reel



SYMBOL	MILLIMETER
A	178±1
B	3.5±0.2
C	14.3±0.2
D	9.8^{+2}_{-1}
E	54.5±0.5
F	12.4±0.5
T1	1.0±0.2
Quantity	10000PCS

BORN SEMICONDUCTOR , INC. ALL RIGHT RESERVED

Specifications are subject to change without notice.
Please refer to http://*www.born-tw.com* for current information.

Revision: 2022-Jan-1-A