SS52-A THRU SS520-A

5.0A Surface Mount Schottky Barrier Rectifiers - 20V-200V

Features


- The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- For surface mounted applications
- Metal silicon junction,majority carrier conduction
- Low power loss,high efficiency
- Built-in strain relief,ideal for automated placement
- High forward surge current capability
- High temperature soldering guaranteed: 250°C/10 seconds at terminals
- Compliant to RoHS Directive 2011/65/EU
- Compliant to Halogen-free

Mechanical data

- **Case**: JEDEC DO-214AC molded plastic body
- **Terminals**: Solder plated, solderable per MIL-STD-750, Method 2026
- **Polarity**: Color band denotes cathode end
- **Mounting Position**: Any

Package outline

SMA/DO-214AC



Dimensions in inches and (millimeters)

Maximum ratings and Electrical Characteristics (AT T_A=25°C unless otherwise noted)

PARAMETER	CONDITIONS	Symbol	MIN.	TYP.	MAX.	UNIT
Forward rectified current	See Fig.2	I_O			5.0	A
Forward surge current	8.3ms single half sine-wave (JEDEC methode)	I_{FSM}			120	A
Reverse current	V_R = V_{RRM} T_A = 25°C	I_R			0.5	mA
	V_R = V_{RRM} T_A = 100°C				10	
Thermal resistance	Junction to ambient NOTE 1	$R_{\theta JA}$		50		°C/W
Diode junction capacitance	f=1MHz and applied 4V DC reverse voltage	C_J		200		pF
Storage temperature		T_{STG}	-65		+150	°C

Note: 1.P.C.B. mounted with 0.2x0.2″(5.0x5.0mm) copper pad areas

SYMBOLS	V_{RRM} *1 (V)	V_{RMS} *2 (V)	V_R *3 (V)	V_F *4 (V)	Operating temperature T_J, (°C)
SS52-A	20	14	20	0.55	-55 to +150
SS53-A	30	21	30		
SS54-A	40	28	40		
SS55-A	50	35	50	0.70	
SS56-A	60	42	60		
SS58-A	80	56	80	0.85	
SS510-A	100	70	100		
SS515-A	150	105	150	0.92	
SS520-A	200	140	200		

*1 Repetitive peak reverse voltage

*2 RMS voltage

*3 Continuous reverse voltage

*4 Maximum forward voltage@I_F=5.0A

http://www.anbonsemi.com
TEL:+86-755-23776891
FAX:+86-755-81482812

Document ID	Issued Date	Revised Date	Revision	Page.
AS-3060019	2003/03/08	2022/05/16	F	3

SS52-A THRU SS520-A

5.0A Surface Mount Schottky Barrier Rectifiers - 20V-200V

Rating and characteristic curves

FIG. 1- FORWARD CURRENT DERATING CURVE




FIG. 2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG. 3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 4-TYPICAL REVERSE CHARACTERISTICS




FIG. 5-TYPICAL JUNCTION CAPACITANCE





FIG. 6-TYPICAL TRANSIENT THERMAL IMPEDANCE




SS52-A THRU SS520-A

5.0A Surface Mount Schottky Barrier Rectifiers - 20V-200V


Pinning information

Pin	Simplified outline	Symbol
Pin1 cathode Pin2 anode		

Marking

Type number	Marking code	Example
SS52-A	SS52	
SS53-A	SS53	
SS54-A	SS54	
SS55-A	SS55	
SS56-A	SS56	
SS58-A	SS58	
SS510-A	SS510	
SS515-A	SS515	
SS520-A	SS520	

Suggested solder pad layout



Dimensions in inches and (millimeters)

PACKAGE	A	B	C
SMA	0.110 (2.80)	0.063 (1.60)	0.087 (2.20)