产品编号 : 2200291025

Product Description : Micro-One Wire-to-Board Header, Vertical, 2.00mm Pitch, Single Row, Glow-Wire Capable, Through Hole, 2 Circuits, Tin-Bismuth Plating, Black, with Potting Capability

系列号 : 220029

状态 : Active

Product Category : PCB Headers and Receptacles



文件和资源

图纸

图纸 2200291025_sd.pdf

3D 模型和设计文件

2D 图纸 DXF 2200291025.dxf

2D 图纸 DXF PDF 2200291025.pdf

3D模型 2200291025_stp.zip

规格

应用规格 2059790000-AS-000.pdf

包装规格 2200299200-SPK-200.pdf

产品规格 2059790000-PS-000.pdf

产物环境合规

合规

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)3788-DC (14 Jun 2023)
EU RoHS	Compliant per EU 2015/863

多部分产品合规性声明

- Eu RoHS
- REACH SVHC

- Low-Halogen

多部分行业合规性文件

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

欧盟 RoHS 合格证书

产品详情

常规

状态	活动
类别	PCB Headers and Receptacles
系列	220029
说明	Micro-One Wire-to-Board Header, Vertical, 2.00mm Pitch, Single Row, Glow-Wire Capable, Through Hole, 2 Circuits, Tin-Bismuth Plating, Black, with Potting Capability
应用	Signal, Wire-to-Board
元件类型	PCB Header
产品系列	Micro-One Wire-to-Board Connector System
产品名称	Micro-One
UPC	196823228780

机构

UL	E29179

电气

每触点最大电流	4.0A
电压 - 最大	250V AC (RMS)/DC

物理

断开	否
回路数（已载入）	2
电路数（最多）	2

颜色-树脂	黑色
耐用性(插拔次数) - 最多次数	30
先接后断	否
阻燃性	94V-0
符合灼热丝规范	是
锁定插接部位	是
材料 - 金属	Brass
材料 - 接合部位电镀	Tin-Bismuth
材料 - 树脂	Liquid Crystal Polymer
净重	689.200/mg
行数	1
方向	垂直
包装形式	Tray
PC 焊脚长度	2.90mm
PCB 保持力	是
间距 - 插配接口	2.00mm
PCB 极性	是
有护墙的	Fully
运行温度范围	-40° to +105° C
终端界面类型	Through Hole

可配插/可连接使用的产品

可配插部件

描述	产品编号
Micro-One Wire-to-Board Receptacle Housings	205979
Micro-One Single Row Receptacle Housings	212724